

Model #	Gear Ratio (X:1)	Rated Output Torque (in-lb)	Max Output Torque (in-lb)	Maximum Input Speed (RPM)	Stages	Backlash Maximum (arcmin)	L1 Length (mm)	L2 Length (mm)	Weight (lbs)
GBPH-0901-CS-003-xxxx-yyy	3	1239	3717	2600	1	11	172	26	7.7
GBPH-0901-CS-004-xxxx-yyy	4	1487	4461	2600	1	11	172	26	7.7
GBPH-0901-CS-005-xxxx-yyy	5	1372	4116	2600	1	11	172	26	7.7
GBPH-0901-CS-007-xxxx-yyy	7	1469	4408	2900	1	11	172	26	7.7
GBPH-0901-CS-010-xxxx-yyy	10	1239	3717	2900	1	11	172	26	7.7
GBPH-0902-CS-012-xxxx-yyy	12	1239	3717	3200	2	16	198	52	9.9
GBPH-0902-CS-015-xxxx-yyy	15	1487	4461	3200	2	16	198	52	9.9
GBPH-0902-CS-016-xxxx-yyy	16	1487	4461	3200	2	16	198	52	9.9
GBPH-0902-CS-020-xxxx-yyy	20	1487	4461	3200	2	16	198	52	9.9
GBPH-0902-CS-021-xxxx-yyy	21	1239	3717	3200	2	16	198	52	9.9
GBPH-0902-CS-025-xxxx-yyy	25	1487	4461	3200	2	16	198	52	9.9
GBPH-0902-CS-028-xxxx-yyy	28	1469	4408	3200	2	16	198	52	9.9
GBPH-0902-CS-030-xxxx-yyy	30	1239	3717	3200	2	16	198	52	9.9
GBPH-0902-CS-035-xxxx-yyy	35	1469	4408	3200	2	16	198	52	9.9
GBPH-0902-CS-040-xxxx-yyy	40	1487	4461	3200	2	16	198	52	9.9
GBPH-0902-CS-049-xxxx-yyy	49	1558	4673	3200	2	16	198	52	9.9
GBPH-0902-CS-050-xxxx-yyy	50	1372	4116	3600	2	16	198	52	9.9
GBPH-0902-CS-070-xxxx-yyy	70	1469	4408	4200	2	16	198	52	9.9
GBPH-0902-CS-100-xxxx-yyy	100	1469	4408	4200	2	16	198	52	9.9
GBPH-0903-CS-036-xxxx-yyy	36	1558	4673	6000	3	16	224	78	12.1
GBPH-0903-CS-045-xxxx-yyy	45	1558	4673	6000	3	16	224	78	12.1
GBPH-0903-CS-060-xxxx-yyy	60	1558	4673	6000	3	16	224	78	12.1
GBPH-0903-CS-075-xxxx-yyy	75	1558	4673	6000	3	16	224	78	12.1
GBPH-0903-CS-080-xxxx-yyy	80	1558	4673	6000	3	16	224	78	12.1
GBPH-0903-CS-090-xxxx-yyy	90	1558	4673	6000	3	16	224	78	12.1
GBPH-0903-CS-150-xxxx-yyy	150	1558	4673	6000	3	16	224	78	12.1
GBPH-0903-CS-200-xxxx-yyy	200	1558	4673	6000	3	16	224	78	12.1
GBPH-0903-CS-300-xxxx-yyy	300	1558	4673	6000	3	16	224	78	12.1
GBPH-0903-CS-400-xxxx-yyy	400	1558	4673	6000	3	16	224	78	12.1
GBPH-0903-CS-500-xxxx-yyy	500	1558	4673	6000	3	16	224	78	12.1
GBPH-0903-CS-700-xxxx-yyy	700	1558	4673	6000	3	16	224	78	12.1
GBPH-0904-CS-1000-xxxx-yyy	1000	1558	4673	6000	4	16	251	115	12.1

Part numbers are based on the specifications of the motor being matched to the gearbox.

-xxxx denotes motor pilot, -yyy denotes input shaft diameter.

Refer to *Matching the Gearbox to Your Motor* on the first page for more information, or contact an Anaheim Automation Applications Engineer for assistance.

Radial Load:	359 lbs. - Force	Axial Load:	1012 lbs. - Force
Operating Temperature:	-15° - 90° C	Noise Level:	64 dB
Efficiency:	3~10: ≥ 97; 12~100: ≥ 94; 150~1000: ≥ 95	IP Rating:	IP65

Matching the Gearbox to Your Motor

To ensure compatibility with the gearbox, it is important to consider that the motor specifications are within the listed ranges below. Motor Bolt Circle Diameter, Input Shaft Diameter, Input Shaft Length, Pilot Thickness, Pilot Diameter and Hole Diameter are required in order to match the motor with the appropriate gearbox, and will be used to determine the complete part number. Please see the Gearbox Mounting form downloadable from our website under *Support - Technical Support - Installations* for more information on required motor data.

Parameter	Range
Bolt Hole Circle Diameter	70mm to 100mm
Input Shaft Diameter	12.7mm to 19mm
Input Shaft Length	40mm Max
Pilot Thickness	8mm Max
Pilot Diameter	50mm to 80mm
Hole Diameter	Any Size