


TSFNA35 Series Linear Actuators



FEATURES

- **Competitively Priced, High Resolution Digital Non- Captive Linear Actuators**
- **Linear Force up to 12.4 lbs (55N)**
- **Linear Step Resolution of 0.001", 0.002", and 0.003"**
- **Unipolar and Bipolar Coil Constructions**
- **Fast, Powerful and Precise Positioning**
- **Precision Radial Ball Bearing Design**
- **Industry Standard Frame Size**
- **Customized Designs Available**
- **CE Certified, RoHS Compliant**




DESCRIPTION


The TSFNA35 Series Non-Captive Linear Actuators are the perfect choice for cost-effective linear motion. The stepper motor internally converts rotary motion to linear motion via a rotating nut and a leadscrew. This actuator eliminates the need for other rotary-to-linear conversions such as belt and pulleys, rack and pinions, or external ball screws. Motion designs can be simplified, production costs lowered and product life enhanced. The motors can be customized to fit your machine requirements. The motor comes in a standard 6-lead configuration and is available in a 4-lead configuration. We can also customize the winding to perfectly match your voltage, current, and maximum operating speed. Special screw modifications, cables and connectors are also available upon request.

SPECIFICATIONS

Model #	Maximum Force (lbs)	Rated Voltage (V)	Travel Per Step (in)	Maximum Travel (in)	The Mark Thrust (N)	The Mark Pull (N)	Resistance Per Phase (ohm)	Inductance Per Phase (mH)	Current Per Phase (A)	Weight (oz)
TSFNA35-150-18-046-LW4	12.4	5	0.001	2.95	55	55	11	8.6	0.46	3.0



Number of Phases:	2-Phase
Insulation Resistance:	100 M-ohms
Protection Rating:	IP34
Bearing Type:	Radial Ball
Operating Temperature Range:	-40°C to 125°C
Storage Temperature Range:	-40°C to 85°C



L010597